

SPECIFICATIONS

SPECIFICATIONS



	6100H	6200H	8200 M	8200 T	8250 M	8250 T	8500 SC	8555 SC	9500	9500 SC	1010	1010 SC
Chute	Swivel	Swivel	Swivel	Swivel	Swivel	Swivel	Swivel	Swivel	Side	Swivel	Side	Swivel
Dual Chop	No	No	No	No	Yes	Yes	No	Yes	No	No	No	No
Silage	No	No	Yes	Yes	No	No	Yes	No	Yes***	Yes***	Yes***	Yes***
Straw	Spread	Spread	Spread	Spread	Chop/Spread	Chop/Spread	Yes	Yes	Yes	Yes	Yes	Yes
Crossbeaters	1	1	1	1	1	1	1	1	2	2	2	2
Capacity (m³)	1.7	2.5	3.2	3.2	3.2	3.2	4.5	4.5	8.0	8.0	10.0	10.0
No. of 5' round bales	1	1	2	2	2	2	2	2	3	3	3***	3***
No. of 8' rect' bales (4'x 2'6"/ 4'x4')	0.5	1/1	1/1	1/1	1/1	1/1	1/1	1/1	2/1	2/1	4/2	4/2
Bale chamber (tailgate down) W x H x L	1.27 x 0.8 x 1.24	1.43 x 1.20 x 2.90m	1.43 x 1.35 x 3.00m			1.43 x 1.35 x 3.00m		1.70 x 1.25 x 2.98m		1.70 x 1.55 x 4.00m		1.70 x 1.58 x 5.70m
Blow distance (max.)	12m	13.5m	20m	20m	20m	20m	22m	22m	25m	22m	25m	22m
Min. tractor PTO HP	70HP	80HP	140HP	60HP	150HP	80HP	80HP	80HP	80HP	80HP	80HP	80HP
Overall width (chute closed)	◆1.72÷1.80m	1.69m	1.87m	2.03m	1.87m	2.03m	2.16m	2.16m	2.49m	2.21m	2.42m	2.42m
Overall length (tailgate up)	2.43m	2.70m	3.02m	4.12m	3.02m	4.12m	4.14m	4.14m	5.2m	5.2m	6.17m	6.17m
Overall length (tailgate/bale clamp down)	2.69m	4.0m	4.88m	5.98m	4.88m	5.98m	5.38m	5.38m	6.33m	6.33m	7.96m	7.96m
Overall height (chute closed)	2.05m	2.52m	2.43m	2.57m	2.43m	2.57m	2.77m	2.77m	2.9m	2.9m	2.93m	2.93m
Unladen weight	◆777÷858kg	1510kg	2022kg	2213kg	2166kg	2357kg	2080kg	2415kg	3007kg	3017kg	3580kg	3590kg
Tyre size	N/A	N/A	N/A	10.00/75-15.3	N/A	10.00/75-15.3	12.50/80-15.3		305/55 R22		385/55 R22.5	
Oil flow rate (min/max) (l/min)	40 - 75	60 - 120	35 - 60	35 - 60	35 - 60	35 - 60	35 - 60	35 - 60	35 - 60	35 - 60	35 - 60	35 - 60

◆ = standard machine ◊ = with bale clamp fitted

Standard/Optional Equipment	6100H	6200H	8200M	8200T	8250M	8250T	8500 SC	8555 SC	9500	9500 SC	1010	1010 SC
Side discharge chute	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	■	N/A	■	N/A
Hydro shield	N/A	N/A	□	□	□	□	□	□	□	□	□	□
Tailgate Extension	N/A	N/A	N/A	N/A	N/A	N/A	□	□	□	□	■	■
In-Line High Pressure Filter	N/A	□	□	□	□	□	□	□	□	□	■	■
Clevis Drawbar & Jack	N/A	N/A	N/A	□	N/A	□	□	□	□	□	□	□
Wide Angle PTO	N/A	N/A	N/A	□	N/A	□	□	□	□	□	□	□
Swivel Chute Extension	N/A	N/A	□	□	□	□	□	□	□	□	□	□
Auto Chain Lubrication	N/A	N/A	□	□	■	■	□	■	□	□	□	□
Ski-Jump Chute	N/A	□	□	□	□	□	□	□	N/A	□	N/A	□
SYNCHRO Control	N/A	N/A	■	■	■	■	N/A	N/A	N/A	N/A	N/A	N/A

Key: □ Optional Equipment ■ Standard Specification N/A Not Available

The company's policy is one of continuous improvement and development, therefore specifications are subject to change without prior notice.