



CUMMINGS & BRICKER

www.cummingsandbricker.com
support@cummingsandbricker.com

PENDULUM TYPE POST HOLE DIGGERS



ED32 & ED44

- Auger sizes available are 6", 9" & 12"
- ED32 digs 32" deep & is to be used w/ 13 to 25 PTO H.P. tractors
- ED44 digs 44" deep & fits Category I, 3-Point Hitch tractors
- ED diggers have 2 ½" steel pipe frame & a 5-year limited warranty for the 30 H.P. gearbox
- DO NOT EXCEED 540 RPM PTO SPEED



XL44A

- Fits Category I, 3-Point Hitch tractors
- Auger sizes available are 6", 9", 12", 14", 18" & 24"
- Bolt-on hard surfaced edges easily removed for sharpening or replacement on auger sizes up to 12"
- Crane size is 3" pipe w/ a 1500lb. lift capacity
- Heavy duty drive shaft protected by shear pin
- Optional scarifier tip for digging loose rock is avail. for 9" & 12" augers
- DO NOT EXCEED 540 RPM PTO SPEED



ECO44

- ECO44 digs 44" deep
- Recommended for 6" & 9" augers
- ECO44 digger has a 5-year limited warranty for the 30 H.P. gearbox
- 2 ½" steel pipe frame
- DO NOT EXCEED 540 RPM PTO SPEED



BR75 & XL44H

- Auger sizes available 6", 9", 12", 14", 18" & 24"
- Bolt-on hard surfaced edges easily removed for sharpening or replacement augers available up to 12"
- BR75 - Heavy duty 90 H.P. gearbox XL44H – Medium Duty 50 H.P. gearbox – both have a 5-year limited warranty
- Lift Crane is made of 3" steel pipe that will lift up to 2,000 lbs. w/o damage to crane & comes w/ guiding lever for easy auger positioning
- Heavy duty drive line is designed for long life. A shear pin, located in power shaft for easy replacement, protects digger & tractor
- Optional Slip Clutch for added gearbox protection
- Category I & II 3-Point Hitch
- DO NOT EXCEED 540 RPM PTO SPEED