BALE WRAPPERS

Z560 The Diamond Z560 3-point mounted machine is also an economical solution for farmers wrapping fewer than 400 bales a year. Maximum bale diameter is 4'x4' and maximum bale weight is 1,800 lbs. The bale is unloaded by raising the table with the 3 point lift. Film is cut with a simple and effective cut and hold feature. A monitor indicates the number of current wraps when working. 20" film may also be used with a minor adjustment. Wrapping time per bale is approximately 80 seconds with 30" film. An optional off load ramp with end tip is available. The machine is designed to operate in a stationary position with the table resting on the ground.

CAT II 3 Point Hitch - Minimum tractor of 45 HP is required to lift the machine alone.



COUNTER DISPLAY
Displays the number of wraps per bale.

OPTIONAL OFF LOAD RAMP
Shown with optional off load ramp with end tip.



CUT-N-HOLD
Simple & effective





ROTARY TABLE
Two rollers for stability & guidance and embossing on the wrapping drums to prevent bales from slipping.

Bale Size	4' x 4'
Maximum Bale Weight	1800 lbs.
Width of Film	30"
Minimum Horse Power	45 HP
Length	8.5 feet
Width	4 feet
Height	5.6 feet
Weight	950 lbs.



Z560 USER REVIEW

"We chose the Diamond over other models because the Diamond did not require the operator to manually tie plastic, count wraps, and manually cut the plastic. Works very well with minimum base tractor to operate it.

We have noticed a marked improvement in herd health and calving success by feeding better quality silage hay especially during calving. It also gives us the ability to make an earlier first cutting and pickup an extra end of season cutting, increasing our over-all yield. It's simple to operate and no adjusting needed once plastic is loaded."

– Morrison Family Farm, Freeport PA

Diamond
By Metal-Fach

DISTRIBUTOR:
CUMMINGS AND BRICKER, INC.
Batavia, NY | Carlisle, PA
Phone 800-252-1552 | 800-222-8969
www.cummingsandbricker.com