




CUMMINGS & BRICKER

www.cummingsandbricker.com
support@cummingsandbricker.com

Effective: 01/23/2024

Revised: 09/01/2025

F.O.B. C&B



Diamond

[Click here for ordering programs-Select Program #2 from Bookmarks](#)

DIAMOND BALE WRAPPER

STATIONARY 3 POINT HITCH DIAMOND BALE WRAPPER

ITEMNUMBER	DESCRIPTION	WEIGHT	PRICE
Z560	Bale Wrapper- CAT II 3 Point Stationary Cable Controls/Monitor (The Machine Is Recommended For Users Wrapping 400 Or Fewer Bales Per Year- 4'x4' Bales)	1100	\$6,714.00
Z560RAMP	Optional Off Load Ramp With End Tip For Z560 Wrapper		\$936.00

The model Z560 3 point mounted machine is an economical solution for farmers wrapping fewer than 400 bales a year. Maximum bale diameter is 4'x4' and maximum bale weight is 2200#. The bale is unloaded by raising the table with the 3 point lift. Film is cut manually. A monitor indicates the number of current wraps when working. 20" film may also be used with a minor adjustment. Wrapping time per bale is approximately 80 seconds with 30" film. An optional off load ramp with end tip is available. The machine is designed to operate in a stationary position with the table resting on the ground.

CAT II 3 Point Hitch - Minimum tractor of 45 HP is required to lift the machine alone.



Shown with optional off load ramp with end tip





CUMMINGS & BRICKER

www.cummingsandbricker.com
support@cummingsandbricker.com

Effective: 01/23/2024

Revised: 09/01/2025

F.O.B. C&B



Diamond

DIAMOND COMPACT DISC HARROW 3 POINT HITCH DISC

ITEMNUMBER	DESCRIPTION	WEIGHT	PRICE
U740B	High speed compact disc harrow 9'10" - 3 point hitch, packer roller	3960	\$28,983.00

PULL TYPE DISC

ITEMNUMBER	DESCRIPTION	WEIGHT	PRICE
U71045DT	High speed compact disc harrow 14'10" - pull type unit, DD heavy roller, folding	11349	\$76,759.00
U71060DT	High speed compact disc harrow 19'9" - pull type unit, DD heavy roller, folding	12898	\$87,437.00

3 POINT & PULL TYPE DISC ACCESSORIES

ITEMNUMBER	DESCRIPTION	PRICE
PLATFORMT	Platform For Seeder U710 Trailed 4.5 And 6.0 Models - For APV500	\$2,704.00

Designed for optimum soil and residue incorporation the compact disc harrow is a universal tool capable of cultivation depths from 2" to 6". Used after harvest or before planting the harrow doesn't just cover the remaining vegetation but perfectly mulches it with the top layer of soil.

Available as 3 point hitch or pull type

SOIL TYPES/FIELD CONDITIONS

It may be used on all types of soils including those with stones thanks to the rubber shock system. The harrow helps open and mix the soil while the packer packs and compresses the soil. Due to the resistance to clogging the harrow is well suited for the cultivation of tall stubble.

WORKING DEPTH

The working depth of the harrow discs may be adjusted using the tractor's 3 point hitch or the mechanical or hydraulic shaft adjustment mechanism.



Seeder platform available for mounted/semi-mounted cultivator.



DIAMOND COMPACT DISC HARROW

COMPACT DISC SPECIFICATIONS:

	U740	U71045/T	U71060/T
Operating Width	9' 10"	14' 10"	19' 9"
Number of Discs	24	36	48
Diameter of Discs	22"	22"	22"
Number of Tines	24	36	48
Max Depth	7"	7"	7"
Operating Speed	5-9 mph	5-9 mph	5-9 mph
Productivity	7-12 acres/hr	10-16 acres/hr	12-20 acres/hr
Power Requirements	100-140 HP	180-270 HP	200-320 HP



¼" thick x 22" diameter



TYPES OF ROLLERS



PACKER ROLLER:

For all soil types. The roller reinforces the soil in bands to improve the water and gas exchange conditions. This roller is suggested for use on rocky, humid soil with a high organic content. Leaves the soil preconditioned for sowing. This is one of the more universal rollers. The roller beam carries cleaning scrapers made from hardened boron steel.



DD HEAVY ROLLER:

This roller features rings with sharp edges for deeper consolidation of soil. The implement easily breaks chunks of soil, while the sheer weight of the roller drives stones deep into the ground. An excellent roller for heavy and rocky soils with a high organic content. The roller features cleaning scrapers. It reinforces the soil in bands to improve the water and gas exchange conditions.