

R18HD



- 1/2" Wheel thickness
- 10 Green teeth

R25HD



- 3/4" Wheel thickness
- 18 Green teeth

R25HS



- 3/4" Wheel thickness
- 18 Green teeth
- 53° Degree swing angle (40-1/4" of travel)
- Adjustable stabilizing feet

Note: Wiring harness required.

MODELS

Hydraulic Models	Rotor dia	Style	Hitch Type	Motor	GPM	
R18HD						
R18HDMB1015G	18"	DIRECT	MINI BOBCAT	26CC GEAR MOTOR	10 TO 15	
R18HDMS1015G	18"	DIRECT	MINI SKID STEER	26CC GEAR MOTOR	10 TO 15	
R18HDSK1520G	18"	DIRECT	UNIVERSAL SKID STEER	39CC GEAR MOTOR	15 TO 20	
134770-AA	OPTIONAL HOSE PROTECTOR SHIELD					
R25HD						
R25HDSK1620G	25"	DIRECT	UNIVERSAL SKID STEER	50CC GEAR MOTOR	16 TO 20	
R25HDSK2026G	25"	DIRECT	UNIVERSAL SKID STEER	63CC GEAR MOTOR	20 TO 26	
R25HDSK2738P	25"	DIRECT	UNIVERSAL SKID STEER	90CC BENT AXIS PISTON MOTOR	27 TO 38	
134771-AA	OPTIONAL HOSE PROTECTOR SHIELD					
R25HS						
R25HSSK1620G	25"	SWING	UNIVERSAL SKID STEER	50CC GEAR MOTOR	16 TO 20	
R25HSSK2026G	25"	SWING	UNIVERSAL SKID STEER	63CC GEAR MOTOR	20 TO 26	
R25HSSK2738P	25"	SWING	UNIVERSAL SKID STEER	90CC BENT AXIS PISTON MOTOR	27 TO 38	
Wiring Harness	CONSULT PRICE BOOK FOR WIRING HARNESSES STARTING WITH EWKD****					
134780-AA	OPTIONAL HOSE PROTECTOR SHIELD					
134868-AA	OPTIONAL BI-DIRECTIONAL WHEEL					