



HYDRAULIC DUMP TRAILER

Ideal's top-of-the-line Hydraulic Dump Trailer combines rugged durability with advanced functionality to help you efficiently manage your outdoor projects. Whether you're clearing fall leaves or cutting trails, updating your home's landscape or tackling farm chores, our Hydraulic Dump Trailer offers the versatility you need to get the job done.

Robust Construction: Built with a 12-gauge formed steel bed supported by a sturdy, 2" x 3" rectangular steel tube frame.

Impressive Capacity: A 1.5-ton load capacity and generous 24 cubic feet of space is the perfect size for daily tasks or heavy-duty utility jobs.

Hydraulic Power: The double-acting hydraulic hand pump, paired with a single-action 3" x 12" cylinder, allows for smooth and reliable dumping. A hydraulic remote hookup (hose included) for compact utility tractor use allows for even quicker dumping.

Efficient Dumping: The 45° dump angle ensures optimal unloading, making your tasks more efficient and less labor-intensive. The tailgate opens from the top or bottom for easy dumping or adjustable spreading.

Enhanced Maneuverability: The walking beam and tandem axle design enhance load distribution and stability, minimizing wear and tear while improving overall handling.

Versatile Hitch Options: Featuring a standard swivel clevis hitch, with an optional 2" coupler available, you can choose the setup that best suits your towing needs and ensures a secure connection.





Overall Dimensions	
Length	100.5"
Width	54.5"
Height	33.5"
Bed Dimensions	
Length	70"
Width	50"
Height	12"
Construction	
Bed	12 Ga Formed Steel Sides
Frame	1/8" Rectangular Steel Tubing, 2" X 3"
Weight, Approx.	650 Lbs.
Hitch	Swivel Clevis Standard, 2" Coupler Optional
Tires	18 X 8.5 X 8 4-Ply Turf-Style
Axle	Walking Beam Tandem
Capacity	1.5 Ton / 24 Cu. Ft.
Dumping Mechanism	Double Acting Hydraulic Hand Pump CUT Hydraulic Remote Hookup (hose included)
Features	Fold Away Tongue Jack. Single Action 3" X 12" Cylinder. Dump Angle 45°
Part Number	DT15ID
UPC	704496030960

