



### MultiGroomer

The Multi-Groomer renovates and conditions conventional and synthetic footings on horse-riding arenas and tracks. The spring tines give an ultimate mixing effect of the surface. The rear bar roller pulverizes and packs to the desired density, and leaves an attractive patterned finish.

- Heavy duty side rub rails
- Double row of adjustable ripper teeth are offset and have a spacing of 4" (and can also be spaced 6" & 8" apart) as well as a working depth of up to 4"
- The rear two rows of spring tines are offset and the pitch and height can be adjusted with a manual ratchet rack or an optional hydraulic cylinder
- The rear bar roller pulverizes and packs to the desired density



### MultiGroomer OPTIONS


MultiGroomer	MG48	MG60	MG72	MG80	MG96	MG120
Dimensions (WLH)	49 x 68 x 32"	61 x 68 x 32"	73 x 72 x 32"	81 x 72 x 32"	97 x 72 x 32"	121 x 72 x 32"
Working Width	48"	60"	72"	80"	96"	120"
Working Depth	4"	4"	4"	4"	4"	4"
Hitch	CAT I	CAT I	CAT I	CAT I	CAT II	CAT II
Weight (lbs.)	580	690	750	875	945	1,500
Tires	16.5 x 6.5-8		20.5 x 8.0-10			
# of Ripper Teeth	11	15	19	19	23	31
Rear Bar Roller (dia.)	12.75"	12.75"	12.75"	12.75"	12.75"	12.75"
HP Required	15-40	20-40	25-70	30-100	30-100	50-120



CAT I Swivel Hitch



Board Scraper



Saw Tooth Leveling Blade



Tow Hitch



Smooth Roll Water Tank



Hydraulic Lift Axle



Tow Hitch



Smooth Roll Water Tank

### MultiGroomer Pony

Based off the MultiGroomer, the **MULTI-GROOMER PONY** is designed for small utility tractors with 3PH or with the tow option for UTV's.



- 4" working depth
- 8.75" rear bar roller diameter
- CAT I Hitch

MultiGroomer Pony	MGP48	MGP60	MGP72	MGP84
Dimensions (WLH)	46 x 51 x 34"	58 x 51 x 34"	73 x 51 x 34"	85 x 51 x 34"
Working Width	48"	60"	72"	84"
Weight (lbs)	330	385	475	550
Tires	16.5 x 6.5-8	16.5 x 6.5-8	20.5 x 8.0-10	20.5 x 8.0-10
# of Ripper Teeth	11	15	17	19
HP Required	25 MAX	25 MAX	35 MAX	35 MAX

### MultiGroomer Pony OPTIONS



Swivel Hitch CAT I



Leveling Blade



Rear Wheel Kit



Tow Hitch



### RotoGroomer

The PTO-driven RotoGroomer renovates and conditions conventional and synthetic footings with high wax and fiber materials in horse-riding arenas. It is the only solution on those footings when a conventional drag will bunch or plug up.

- Carbide toothed single direction drive rotor
- PTO Driven 540 RPM with slip clutch protection
- 12" rear smooth packing roll with self-adjusting scraper
- Water can be added to rear packer roll for extra weight



RotoGroomer	PTORG72	PTORG96
HP Required	20-80	40-80
Working Width	72"	96"
Height	30"	30"
Weight (lbs)	800	1,000
Hitch	CAT I	CAT II
Drum Speed (RPM)	200	200

### MultiGroomer OPTIONS



Pulverizer Roller



Ripper Bar



Board Scraper



Floating Spill Shield Kit



CAT I Swivel Hitch



CAT II Swivel Hitch



### Drag Mat

- Rolls up behind your bumper to transport with unique crank, folding handle and lock system
- Fits on to any 2" trailer hitch receiver

Drag Mat	DM66	DM84
Dimensions (WLH)	73x20x10"	91x20x10"
Mesh Mat	1" Sq. Stainless Steel Mesh	1" Sq. Stainless Steel Mesh



Optional Drag Mat Hitch Extension

**REIST INDUSTRIES**  
100 Union Street  
Elmira, Ontario, Canada

Phone: 519-669-1501 • Toll Free: 1-877-467-3478  
www.reistindustries.com

DISTRIBUTED BY:



**CUMMINGS & BRICKER, INC.**  
cummingsandbricker.com  
support@cummingsandbricker.com  
800-252-1552