



ROTARY TILLER

IDEAL Farm Equipment's Rotary Tiller can take on the big jobs, able to handle acres of dirt with no worries. This implement boasts thick-steel cutting tines that work hard to break up and mix hardened soil into soft, workable land. The tines can be adjusted to three depth levels, perfect for landscaping, gardening and nurseries.



DESCRIPTION	LIGHT-DUTY 4' ROTARY TILLER	STANDARD DUTY 5' ROTARY TILLER	STANDARD-DUTY 6' ROTARY TILLER
ITEM #	RT4LDID	RT5SDID	RT6SDID
TRACTOR HORSEPOWER REQUIRED	15-35	25-50	30-50
IMPLEMENT TYPE	ROTARY TILLER	ROTARY TILLER	ROTARY TILLER
APPROX. WEIGHT	470 LBS.	638 LBS.	718 LBS.
WIDTH	51.5"	64"	76"
WORKING WIDTH	46.5"	58.75"	70.59"
MAX. WORKING DEPTH	7"	7"	7"
HITCH	LIMITED CAT 1	CAT 1	CAT 1
QUICK HITCH COMPATIBLE	YES	YES	YES
DRIVELINE	540 RPM SLIP CLUTCH PROTECTION	540 RPM SLIP CLUTCH PROTECTION	540 RPM SLIP CLUTCH PROTECTION
ROTOR ROTATION	REVERSIBLE (FWD/REV)	REVERSIBLE (FWD/REV)	REVERSIBLE (FWD/REV)
ROTOR SHAFT SPEED	211 RPM @ 540 RPM PTO	211 RPM @ 540 RPM PTO	211 RPM @ 540 RPM PTO
NUMBER OF FLANGES ON ROTOR	6	7	9
NUMBER OF TINES PER FLANGE	4	6	6
SKID SHOES	ADJUSTABLE (0.4", 1.4", 2.4")	ADJUSTABLE (0.4", 1.4", 2.4")	ADJUSTABLE (0.4", 1.4", 2.4")
TOP GEARBOX CONSTRUCTION	CAST IRON HOUSING, PRECISION FORGED STEEL GEARS	CAST IRON HOUSING, HARDENED STEEL GEARS	CAST IRON HOUSING, HARDENED STEEL GEARS
SIDE GEARBOX CONSTRUCTION	FORMED STEEL HOUSING, HARDENED STEEL GEARS	FORMED STEEL HOUSING, HARDENED STEEL GEARS	FORMED STEEL HOUSING, HARDENED STEEL GEARS
GEARBOX LUBRICATION	EP 80-90W GEAR OIL	EP 80-90W GEAR OIL	EP 80-90W GEAR OIL
MAJOR CONSTRUCTION	-	3/8" SOLID STEEL GEARBOX PLATE AND ENDPLATES, 5/8" STEEL HITCH FRAME	3/8" SOLID STEEL GEARBOX PLATE AND ENDPLATES, 5/8" STEEL HITCH FRAME

