

CONVEY-ALL[®]

STAINLESS STEEL



CONVEY-ALL® TRUCK LOAD CONVEYORS



Truck Load with Rail Car Hopper

16" BELT CONVEYORS

10" Tube
16" Belt
UP TO
9,000BPH

Model	Axle Width	Transport Height	Transport Length	- 20° -		- 25° -		- 30° -	
				Discharge Height	Length	Discharge Height	Length	Discharge Height	Length
1635	8'	10' 11"	40' 8"	11' 6"	37' 1"	14' 8"	35' 10"	17' 9"	34' 5"
1645	9' 1"	11' 8"	50' 10"	14' 11"	44' 7"	18' 11"	43' 5"	21' 9"	41' 10"
1635-FL	7' 11"	10' 5"	43' 7"	10' 9"	36' 7"	14' 1"	35' 7"	17' 4"	34' 4"
1645-FL	8' 4"	11' 5"	53' 7"	14' 2"	46' 1"	18' 5"	44' 8"	22' 1"	42' 11"
1640-TL	8' 4"	9' 7"	43' 9"	10' 9"	40' 9"	14' 1"	39' 10"	17' 4"	38' 4"
1650-TL	8' 4"	11' 5"	53' 7"	14' 2"	46'	18' 4"	44' 8"	22' 4"	43'
1658-TL	8' 4"	12' 10"	60' 8"	16' 9"	53' 1"	21' 6"	51' 6"	26' 1"	49' 6"

22" BELT CONVEYORS

14" Tube
22" Belt
UP TO
12,000BPH

Model	Axle Width	Transport Height	Transport Length	- 20° -		- 25° -		- 30° -	
				Discharge Height	Length	Discharge Height	Length	Discharge Height	Length
2235	8' 4"	10' 8"	38' 8"	10' 11"	33' 6"	13' 11"	32' 8"	16' 9"	31' 7"
2245	9' 1"	11' 3"	48' 9"	13' 9"	42' 10"	17' 6"	41' 8"	21' 1"	40' 2"
2250-TL	8' 4"	13' 6"	51' 6"	12' 9"	44' 3"	16' 10"	43' 1"	20' 10"	41' 7"
2258-TL	8' 4"	15' 4"	58' 10"	15' 4"	51' 7"	20' 1"	50' 2"	24' 7"	48' 4"

Convey-All's series of Truck Load conveyors are perfect for moving product from a bin, and loading into a truck or trailer. Our fully loaded Truck Load (TL) models are self-propelled, meaning the conveyor can drive to the truck, not truck to conveyor. Being self-contained and fully hydraulic, means no dealing with belts, pulleys, chains or sprockets.

STANDARD FEATURES:

- Collapsible hopper
- Full length windguards
- Heavy-duty undercarriages
- Hydraulic lift
- Spring Tension Drive Box

OPTIONS:

- Gas, diesel, electric or PTO drive
- Self-contained drive system
- Mover kit
- Cold weather pkg (16" conveyors)
- Hydraulic oil reservoir heater
- Fender and light package
- 2-5/16" ball receiver hitch
- Quad-adjust hood package
- Heavy-duty, Railcar Hopper

CONVEY-ALL® BIN FILL CONVEYORS



Bin Fill with Swing Out

16" BELT CONVEYORS

Model	Axle Width	Transport Height	Transport Length	- 15° -		- 20° -		- 25° -		- 30° -	
				Discharge Height	Length	Discharge Height	Length	Discharge Height	Length	Discharge Height	Length
1655	11' 4"	9' 9"	61'	13' 5"	55' 2"	18' 4"	54'	23' 2"	52' 5"	27' 9"	50' 6"
1665	11' 4"	10' 8"	71'	16' 2"	64' 7"	22'	63'	27' 4"	60' 11"	32' 8"	58' 5"
1670	11' 4"	11' 10"	75' 11"	17' 4"	69' 8"	23' 6"	68' 1"	29' 6"	66' 1"	35' 3"	63' 6"
1675	11' 4"	12' 5"	80' 11"	18' 9"	74' 6"	25' 3"	72' 10"	31' 7"	70' 7"	37' 8"	67' 10"
1685	12' 6"	11' 7"	91' 1"	21' 5"	84' 2"	28' 9"	82' 3"	35' 11"	79' 8"	42' 9"	76' 6"
1690	12' 6"	12' 2"	96'	22' 7"	89'	30' 4"	86' 11"	37' 11"	84' 2"	45' 3"	80' 10"
16100	13' 6"	14' 7"	105' 10"	25' 3"	98' 8"	33' 10"	96' 4"	42' 2"	93' 3"	50' 2"	89' 6"



UP TO
9,000BPH

22" BELT CONVEYORS

Model	Axle Width	Transport Height	Transport Length	- 15° -		- 20° -		- 25° -		- 30° -	
				Discharge Height	Length	Discharge Height	Length	Discharge Height	Length	Discharge Height	Length
2265	9' 1"	11' 5"	69'	15' 1"	63'	20' 7"	61' 8"	25' 10"	59' 10"	30' 11"	57' 7"
2270	9' 1"	11' 7"	74'	16' 10"	67' 10"	22' 9"	66' 4"	28' 6"	64' 4"	34' 1"	61' 11"
2275	9' 1"	11' 2"	78' 11"	17' 8"	72' 8"	24'	71' 1"	30' 1"	68' 11"	35' 11"	66' 3"
2285	13' 6"	12' 4"	89'	20' 9"	82' 4"	27' 10"	80' 5"	34' 8"	77' 11"	41' 3"	74' 10"
2290	13' 6"	13' 1"	93' 11"	22' 1"	87' 2"	29' 7"	85' 2"	36' 10"	82' 5"	43' 9"	79' 2"
22100	13' 6"	14'	103' 11"	24' 8"	96' 10"	33' 0"	94' 6"	41' 0"	91' 6"	48' 9"	87' 10"
22110	13' 6"	14' 6"	108' 11"	27' 3"	101' 8"	36' 5"	99' 3"	45' 3"	96'	53' 9"	92' 9"
22120	13' 11"	15'	124'	29' 10"	116' 2"	39' 10"	113' 4"	49' 6"	109' 8"	58' 9"	105' 2"



UP TO
12,000BPH

Convey-All® has a complete range of tube conveyor lengths. A size for any job. Our easy moving, long reaching tube conveyors are great for filling bins or making large piles.

Convey-All® conveyors are designed to be efficient and simple to use. The engine and control station are set low for easy access. The undercarriages are rugged and heavy duty, using structural steel and fabricated for bolt-together durability. Combine our Bin Fill Conveyors with a Convey-All® Transfer Conveyor or Swing Out for ultimate efficiency.

STANDARD FEATURES:

- Collapsible hopper
- Full length windguards
- Heavy-duty scissor lift undercarriages
- Positive Pinch Drive Box

OPTIONAL FEATURES:

- Side or end PTO, gas, diesel, electric or hydraulic drive
- Swing Out Package
- Mover Kit
- Hopper lift (on longer 22" conveyors)
- Winch for collapsible hopper
- Hydraulic lift



1616-RC Railcar

2228-DO Drive-Over

1615 Transfer

TRANSFER CONVEYORS

Convey-All® Transfer Conveyors are well balanced, easy to maneuver and position, and come in a variety of configurations to fit your application. The conveyor is complete with a tow package which includes highway tires and hitch. We offer electric, hydraulic or gas drives, and capacities up to 12,000BPH.

Model	Discharge Height to Ground	Hopper to Ground	Overall Length	Hopper Length
1214-GN	36" - 48"	61/2"	15' 4"	4' 9"
1615	38" - 48"	61/2" - 73/4"	17' 4"	5' 10"
1616-RC	36" - 48"	45/8"	20'	7'
2218	38" - 48"	61/2" - 73/4"	20' 2"	5' 10"
2218-RC	36" - 48"	45/8"	21' 6"	7'
2228-DO	3' 2"	8"	29'	9' 6"

CONVEY-ALL®

COUNT ON IT.

convey-all.com | (800) 665-7259